

# ALEXPLAST D30

## Water Reducing Admixture



### Description

**ALEXPLAST D30** is a high water reducing and retarding admixture for concrete. Formulated from synthetic organic chemicals For retarding the initial and final setting that aggressively disperses cement particles which enabling the mixing water to perform more efficiently so it facilitate concrete transported and casted with little vibration.

### Uses

- Pumped concrete.
- In precast and prestressed concrete.
- Ready mixed concrete.
- Casting in hot climates.
- To reduce permeability.
- To produce high workability concrete.

### Advantages

- Produce water proofing concrete.
- Eliminate shrinkage.
- Increase cohesion, minimizes segregation and bleeding and gives improved surface finish.
- Improve physical properties for concrete.
- Free from chlorides, nitrades.
- Increase density and reduces porosity resulting in improved water penetration resistance.
- High quality surface finish.
- Non toxic as it is water based.

- Compatible with all type of ordinary and sulphate resistant cement.
- Compatible with ALEXCHEM other additives(Contact our technical office).

### Standards

**ALEXPLAST D30** complies with ASTM C494 Types A, B, D

### Properties

Colour	Dark Brown liquid	
Specific gravity	1.17	20°C
Chloride content	Nil	
Water Reduction	Reduction up to 12% can be reached depending on materials used and mix design	
Compatibility	Can be used with all types of Portland cements	
Durability	When <b>ALEXPLAST D30</b> is used for water reduction the increase in density and reduction of permeability improved durability and reduces porosity hence increase water proofing properties also resist salts which attack concrete.	

## **Guide to Application**

### **Application**

**ALEXPLAST D30** should be added to the mixing water prior to addition to the dry mix

### **Coverage:**

Approximately 0.3-0.90 per 100 Kg cement.  
A site trial should be carried out to confirm the mix design.

### **Packing:**

Is supplied in 20 lit, 210 lit drums, 1000 lit bulks.

### **Guarantee:**

All precaution is taken in manufacture of each product to comply with the standard of each material.

The data sheet for each product for information only and may be corrected and no liability is accepted for it.

The results may have variation because the method of their use condition under which they are applied cannot be anticipated.

### **Technical Service:**

For any technical advice for using the **ALEXCHEM** contact the technical office.

### **Shelf life:**

Up to 12 month when stored as Recommended

### **Storage:**

Should be stored in shaded areas

### **Safety precaution**

- Avoid contact with eyes, mouth skin, and follow by washing soap and water.

And any eye contamination should be washed thoroughly with plenty of water and immediate medical treatment sought.

## **HEAD OFFICE:**

12 Ibn saad,45 Miami ,Alexandria  
Tel:03-5885431 Fax:03-5885253  
mob: 01155444400  
Website : [www.alexchem.net](http://www.alexchem.net)  
Email : [info@alexchem.net](mailto:info@alexchem.net)

## **FACTORY:**

ElNahda- Amrya -Alexandria  
Tel/Fax:03-4770313