

ALEX PUTTY

High Quality Cementitious Putty

Description

ALEXPUTTY is a single component for filling and adjustment of cementitious surfaces (plaster paint and concrete), also before painting works and other types of finish works.

Uses

- To fill porous and adjustment which required before the final finish work of plastic paint, oil paint, cement paint on its different colours.

Advantages

- Use for internal and external surfaces.
- High cohesive force with plain concrete or cement paint layers.
- Give a smooth final surface, free from cracks and stains.
- Easy to mix and apply.
- Suitable for all kind of paints.
- Economical compared with the other types of polymer base.

Properties

Colour	White, Grey and upon request	
Specific Weight	1.20 kg/lit	
Cure Time	60 min	5-35 °C
Thickness	1-2 mm according to surface nature	

Guide to application

Surface preparation:

- The surface must be clean, free from dust, oils, grease and loose materials, using spraying water to wet the surface.
- The coloured powder is added gradually to 10.0 lit of water and stir well till reaching the homogenous texture and colour.
- Apply to the prepared surface either by conventional hand applied technique or using spraying machine followed by smoothing to desired surface texture. In this case the quality of the mixing water may be increased till flowable consistency will be achieved.
- It is prefer to wet the surface by using automatic sprayer and also prefer to wet the surface before the first layer of painting without leaving excess water.
- It should be immediately applied on the prepared surface while the mortar is fresh and workable. In case of delay do not add additional water, remix till the mortar is workable again.
- It is recommended to apply **ALEXPUTTY** at 2 layers minimum each layer should be left to dry completely for at least 2 hours prior to application of the following layer, pre-wet the first layer before applying the following layer.
- It can be applied at thickness up to 4 mm per layer (max 2 coats per day)

Coverage:

- ½ kg/m² depend on the surface nature and its equality.

Packing:

It is available in 25 kg

Storage:

Up to 12 months if stored out of direct sun according to manufactured instruction

Safety Precaution:

- **ALEXP** is non toxic and not harmful while using.
- Remove any contamination from Skin by water and soap

Guarantee:

All precaution is taken in manufacture of each product to comply with the standard of each material.

The data sheet for each product for information only and may be corrected and no liability is accepted for it.

The results may have variation because the method of their use condition under which they are applied cannot be anticipated.

Technical Service:

For any technical advice for using the **ALEXCHEM** contact the technical office.

HEAD OFFICE:

12 Ibn saad,45 Miami ,Alexandria
Tel:03-5885431 Fax:03-5885253
mob: 01155444400
Website : www.alexchem.net
Email : info@alexchem.net

FACTORY:

EINahda- Amrya -Alexandria
Tel/Fax:03-4770313